

- 631 630 629 628 627 626 625 624 623 622 621 620 619 618 617 616 615 614 613 612 611 610 609 608 607 606 605 604 603 602 601 600 599 598 597 596 595 594 593 592 591 590 589 588 587 586 585 584 583 582 581 580 579 578 577 576 575 574 573 572 571 570 569 568 567 566 565 564 563 562 561 560 559 558 557 556 555 554 553 552 551 550 549 548 547 546 545 544 543 542 541 540 539 538 537 536 535 534 533 532 531 530 529 528 527 526 525 524 523 522 521 520 519 518 517 516 515 514 513 512 511 510 509 508 507 506 505 504 503 502 501 500 499 498 497 496 495 494 493 492 491 490 489 488 487 486 485 484 483 482 481 480 479 478 477 476 475 474 473 472 471 470 469 468 467 466 465 464 463 462 461 460 459 458 457 456 455 454 453 452 451 450 449 448 447 446 445 444 443 442 441 440 439 438 437 436 435 434 433 432 431 430 429 428 427 426 425 424 423 422 421 420 419 418 417 416 415 414 413 412 411 410 409 408 407 406 405 404 403 402 401 400 399 398 397 396 395 394 393 392 391 390 389 388 387 386 385 384 383 382 381 380 379 378 377 376 375 374 373 372 371 370 369 368 367 366 365 364 363 362 361 360 359 358 357 356 355 354 353 352 351 350 349 348 347 346 345 344 343 342 341 340 339 338 337 336 335 334 333 332 331 330 329 328 327 326 325 324 323 322 321 320 319 318 317 316 315 314 313 312 311 310 309 308 307 306 305 304 303 302 301 300 299 298 297 296 295 294 293 292 291 290 289 288 287 286 285 284 283 282 281 280 279 278 277 276 275 274 273 272 271 270 269 268 267 266 265 264 263 262 261 260 259 258 257 256 255 254 253 252 251 250 249 248 247 246 245 244 243 242 241 240 239 238 237 236 235 234 233 232 231 230 229 228 227 226 225 224 223 222 221 220 219 218 217 216 215 214 213 212 211 210 209 208 207 206 205 204 203 202 201 200 199 198 197 196 195 194 193 192 191 190 189 188 187 186 185 184 183 182 181 180 179 178 177 176 175 174 173 172 171 170 169 168 167 166 165 164 163 162 161 160 159 158 157 156 155 154 153 152 151 150 149 148 147 146 145 144 143 142 141 140 139 138 137 136 135 134 133 132 131 130 129 128 127 126 125 124 123 122 121 120 119 118 117 116 115 114 113 112 111 110 109 108 107 106 105 104 103 102 101 100 99 98 97 96 95 94 93 92 91 90 89 88 87 86 85 84 83 82 81 80 79 78 77 76 75 74 73 72 71 70 69 68 67 66 65 64 63 62 61 60 59 58 57 56 55 54 53 52 51 50 49 48 47 46 45 44 43 42 41 40 39 38 37 36 35 34 33 32 31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1
- (21) Application No. 50859/72 (22) Filed 3 Nov. 1972
(31) Convention Application No. 197485 (32) Filed 10 Nov. 1972 in
(33) United States of America (US)
(44) Complete Specification published 4 June 1975
(51) INT CL² D21C 9/14
(52) Index at acceptance
D1P 1A1A4 1A3 1A5 1C1B



(54) BLEACHING OF WASTE PAPER PULP

- (71) We, HOOKER CHEMICAL CORPORATION, a corporation organised and existing under the laws of the State of New York, United States of America, of Niagara Falls, New York, United States of America, do hereby declare the invention for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:—
- This invention relates to a process for bleaching waste paper pulp to a commercially acceptable brightness in a single bleaching step.
- With the increased awareness of the need for environmental stabilization, the recycling of waste paper has become an important issue. Heretofore, waste paper recycling processes have been deemed economically non-commercial owing to the relatively high cost of cleaning, de-inking, and bleaching thereof. Recently however technological advances have been made in the areas of commercial cleaning and de-inking processes which have provided a more economical and better grade of waste paper pulp. As a result, increased quantities of waste paper pulp have become available to the paper industry for recycling purposes, but, utilization thereof has been precluded by the high cost and complexity of equipment and chemicals necessary for bleaching by conventional methods.
- High requirements are placed on the purity of the products obtained when manufacturing bleached, waste paper pulp. A large majority of the impurities found in the finished product originate from printer inks and dyes, pigments or discolored fiber bundles. The extent to which the pulp is freed from the aforementioned impurities depends partly upon how well the de-inking-cleaning operations are carried out.
- There are many methods of de-inking and/or cleaning waste paper pulp. In one de-inking and cleaning process, old magazine stock, newspapers, broke, small quantities of groundwood (up to about 7%), and various waste papers containing a large number of coated cellulosic fiber materials, are first treated in any suitable manner to divide the paper into relatively small pieces. The paper is then subjected to a preliminary treatment with a solvent for the removal of, for example, resins, bitumin and tar, and also colored inks, by introducing the waste paper into a hopper and passing a solvent such as benzol, carbon tetrachloride, or trichloroethylene through the body of the paper, the solvent being recovered for re-use. Water is then added so as to form a dilute aqueous suspension, and various additives may be added, for example to reduce surface tension. The mass is then washed, screened, dried or otherwise prepared for storage prior to the bleaching processes.
- As indicated above, the purity of the pulp depends upon how well the de-inking and/or cleaning operations have been carried out. Naturally economic factors limit the extent to which the pulp can be subject to purification by these means, and it has been shown in practice that a purified pulp, which has been subjected to the most careful de-inking and/or cleaning techniques, always contains a certain amount of color and impurities, mainly due to the presence of ink traces.
- The principal intention, when bleaching waste paper pulp, is to increase the brightness of the pulp by oxidizing ink traces and other impurities, without appreciably lowering the viscosity of the cellulosic stock and with a minimal retention time in the bleaching apparatus. This is often effected by means of a sequence of bleaching stages, including treatments using, for example chlorine, hypochlorite, chlorine dioxide, or alkali. Oxidation of the impurities is most easily effected using discrete fibers which are more freely accessible to the influence of the bleaching chemicals.
- It is apparent from the foregoing, that, in addition to expecting a brighter pulp from the bleaching process, a cleaner pulp is also anticipated, i.e. a pulp with less colored impurities than in the case of the unbleached pulp. In view of the present high requirements placed on the brightness of the bleached

pulp, the ability of the bleaching process to brighten the pulp is of great importance. In many cases as fed as 10 specks of insufficiently bleached impurities per square meter of sheet pulp may lead to such depreciation in the quality of the pulp that the pulp must be sold at a reduced price.

It has been known to bleach virgin cellulosic pulp with chlorine or chlorine dioxide, either separately or in a mixture. Chlorine bleaching of virgin pulp is usually effected at low temperatures (preferably below 70°F) and with low consistency (2.5—4.5%) and in short bleaching periods (30—90 minutes). The low pulp consistency is desirable for two reasons, firstly, to obtain a rapid, uniform intermixing of the chlorine in a pulp suspension which is necessary for obtaining a uniform chlorination of the pulp during the rapid reaction which takes place between the chlorine and lignin, and, secondly, to avoid sharp rises in temperatures in the pulp suspension owing to the strong exothermic reaction between chlorine and lignin, since high temperatures in chlorine bleaching lead to an uncontrollable oxidative decomposition of the pulp. Chlorine dioxide bleaching of virgin pulp is usually effected at high temperatures (80—180°F), higher consistencies (4.0—12.0%) and longer bleaching periods (3—6 hours) because of its lower oxidation potential. On the other hand, the bleaching of recycled, waste paper pulp has been limited in the prior art to chlorine or hypochlorite processes. Chlorine dioxide is considered a milder bleaching agent than chlorine or hypochlorite and the presence of difficult-to-bleach printer's ink and various other colored and paper coating impurities within the waste paper pulp reduce the effectiveness of chlorine dioxide as a bleaching agent. Further, in view of the presence of these difficult-to-bleach impurities, one would expect to utilize greater amounts of chlorine dioxide, at higher unit cost and longer bleaching time periods, to obtain a brightness approaching, but inferior, to that obtainable with Cl_2 or hypochlorite.

The present invention provides a process whereby recycled waste paper pulp can be bleached to a higher level of brightness, utilizing commercial viscosities, together with unexpectedly short retention times in the chlorinating apparatus, at a decrease in commercial cost in a single bleaching step wherein an aqueous mixture of the pulp is contacted with chlorine dioxide as the sole bleaching agent. The waste paper pulp is preferably contacted with up to about 1.0% by weight ClO_2 , equivalent to about 2.64% Cl_2 , so as to obtain a brightness of up to 92% (as determined by the standard TAPPI test) while maintaining a minimal viscosity change in the pulp stock. This demonstrates that ClO_2 is an effective bleaching agent for the treatment of waste paper pulp.

A wide temperature range is acceptable for the pulp suspension during the bleaching process. The temperature used would depend mainly upon the equipment available in a given mill. The process can be operated at relatively low or high temperatures, the process taking a shorter time at high temperatures and an extended time at low temperatures. The temperature range is preferably from 50°F to 180°F, depending on the mill equipment. A range of 140°F to 180°F, has been found to be particularly preferred. The heating of the pulp suspension may take place during or after its preparation by, for example, sparging in live steam or hot water.

The bleaching process is preferably conducted at a pH of about 2 to about 5, and most advantageously conducted at a pH of about 3 to about 4. While the pH of the aqueous pulp suspension should be maintained close to these stated ranges throughout the bleaching step, adjustment thereof may be accomplished before or concurrently with the addition of ClO_2 bleaching agent. The pH may be adjusted by the addition of acids, or of alkalis, such as caustic soda.

Despite the above described degrees of freedom in the matters of the timing and manner of adjustment of the pH, it has nevertheless been found somewhat advantageous to adjust the pH of the suspension preliminarily to certain specified values prior to the addition of the bleaching agent. The purpose of such preliminary adjustment of the pH is to ensure that as much as possible of the bleaching agent is consumed within the above mentioned ranges and, conversely, to ensure that as little as possible of the bleaching agent is flashed off under reduced pressure and wasted. Thus, the pH is preferably adjusted to about neutrality prior to the addition of the bleaching agent to the pulp suspension. Following the preliminary pH adjustment and the addition of the bleaching agent for the bleaching step, some further adjustment may be required to bring the suspension pH within the specified range for the bleaching process.

The waste paper pulp used in the bleaching process of this invention can conveniently contain up to 7% by weight groundwood.

Upon completion of the bleaching process the bleached pulp after a washing step, may be fed into the paper mill system together with normal pulp going to the paper machine. Due to the effectiveness of the bleaching process of this invention the bleached pulp can be dyed any color. Heretofore it was necessary to select a particular bleached pulp that could be used to furnish a particular color. This obviously, is of importance in regard to handling costs in quality control. The bleached pulp may also be stored in the aqueous or oven dried state for later use. The process of this invention displays a

further superiority over the prior art Cl_2 or hypochlorite processes in that later loss of brightness is less acute with the process of this invention as compared to the prior art.

- 5 The following examples serve to illustrate the invention; all parts and percentages are on a weight basis.

EXAMPLE I

- 10 Water was added to a quantity of oven dried, unbleached de-inked, commercial waste paper pulp so as to form an aqueous pulp mixture having a consistency of 3.5% cellulose fibers/96.5% water. The aqueous pulp mixture was then divided into separate
- 15 samples, each sample with sufficient aqueous pulp mixture to contain 25 grams of the cellulosic fiber component. Viscosity, pH and Brightness were then determined using standard TAPPI tests with the following
- 20 results:

Viscosity	15.1 cp
pH	7.0
Brightness	78.9

EXAMPLE II

- 25 A sample (containing 25 grams of the cellulosic fiber component) of the aqueous pulp mixture of Example I, was subjected to the following two-phase bleaching sequence:

- 30 First phase:

- 35 Sufficient 0.5 $\text{Cl}_2/\text{H}_2\text{O}$ solution was added to a covered container, along with said sample, so as to form a solution therewith containing 0.3% Cl_2 calculated as weight percent of cellulosic fiber component. The solution was thereafter allowed to react, without agitation, at 80°F, for 10 minutes.

Second phase:

Immediately at the end of the 10 minute reaction time period of the first phase, 2.0% NaOH solution was added to the reaction product so as to form a solution therewith containing 0.6% NaOH, calculated as weight percent of the cellulosic fiber component. The solution was thereafter allowed to react, without agitation, at 80°F, for 30 minutes

At the completion of the 30 minute reaction time period of the second phase, the pulp was tested using the standard TAPPI tests of Example I with the following results:

Viscosity	14.7
pH	11.2
Brightness	86.6

1 hour after the completion of the 30 minute reaction time period of the second phase, the pulp was tested for brightness using the standard TAPPI test of Example I with the following results:

Brightness	85.5
------------	------

18 hours after the completion of the 30 minute reaction time period of the second phase, the pulp was tested for brightness using the standard TAPPI test of Example I with the following results:

Brightness	83.9
------------	------

EXAMPLE III—X

- 70 Samples (containing 25 grams of the cellulosic fiber component) of the aqueous pulp mixture of Example I were subjected to the two phase bleaching sequence of Example II with the following modification and results:

		First Phase		Second Phase		Brightness			
		% Cl_2	Reaction Time	%NaOH	Reaction Time	Viscosity	pH	Final	1 Hr. 18 Hr.
75	Ex. III	0.3	10	0.6	60	14.8	11.3	87.7	86.6 84.3
	Ex. IV	0.3	10	0.6	90	14.6	11.1	87.2	86.0 84.1
	Ex. V	0.5	10	0.8	60	14.7	11.5	88.2	87.0 85.1
	Ex. VI	0.5	10	0.8	30	14.7	11.4	86.6	85.6 83.9
80	Ex. VII	0.5	10	1.0	60	14.7	11.3	88.2	86.9 85.0
	Ex. VIII	0.5	5	1.0	60	14.7	11.2	88.7	87.5 85.7
	Ex. IX	1.0	5	1.5	60	13.8	11.0	88.5	87.0 85.1
	Ex. X	1.5	5	2.0	60	13.3	10.2	89.1	87.4 85.4

EXAMPLE XI

- 85 Water was added to a quantity of oven dried, unbleached, de-inked, commercial waste paper pulp of Example I as to form an aqueous pulp mixture having a consistency of 4.0% cellulosic fiber/96.0% water the aqueous
- 90 pulp mixture was then divided into separate samples, each sample having sufficient aqueous pulp mixture to contain 25 grams

of the cellulosic fiber component. Standard TAPPI testing indicated that viscosity, pH and Brightness of the three samples were the same as in Example I.

A sample (containing 25 grams of the cellulosic fiber) of the aqueous pulp, as above prepared, was placed in a covered container, along with sufficient 0.5% $\text{ClO}_2/\text{H}_2\text{O}$ solution to form a solution containing 0.114%

5 ClO_2 (equivalent to 0.3% Cl_2) calculated as weight percent of cellulosic fiber component. The solution was allowed to react, without agitation, at 160°F, for 180 minutes. At the completion of the 180 minute reaction time period, the pulp was tested using the standard TAPPI test of Example I with the following results:

10 Viscosity 14.4
 pH 5.8
 Brightness 90.4

1 hour, and 18 hours after the completion

25

	Equivalent To		Viscosity	pH	Final	Brightness	
	% ClO_2	% Cl_2				1 Hr.	18 Hr.
Example XII	0.19	0.5	14.4	5.4	90.4	89.8	88.0
Example XIII	0.38	1.0	13.7	4.3	90.7	90.0	88.7

WHAT WE CLAIM IS:—

- 30 1. A process for bleaching waste paper pulp in a single bleaching step which comprises contacting an aqueous mixture of the pulp with chlorine dioxide as the sole bleaching agent.
- 35 2. A process according to claim 1, wherein the pulp is bleached at from 50°F. to 180°F.
3. A process according to claim 2, wherein the pulp is bleached at from 140°F. to 180°F.
- 40 4. A process according to any one of the preceding claims, wherein the pulp is contacted with up to 1.0% by weight chlorine dioxide.
5. A process according to any one of the preceding claims conducted at a pH from 2 to 5.
- 45 6. A process according to claim 5 conducted at a pH from 3 to 4.
7. A process according to any one of the preceding claims in which the aqueous mix-

of the 180 minute reaction time period, the pulp was tested for brightness using the standard TAPPI tests of Example I with the following results: 15

Brightness	1 Hour	18 Hours
	89.5	87.7

EXAMPLES XII—XIII

20 Samples (containing 25 grams of the cellulosic fiber component) of the aqueous pulp mixture were prepared and bleached in accordance with Example XI with the following modifications and results:

ture of pulp is neutralised before it is contacted with the chlorine dioxide. 50

8. A process according to any one of the preceding claims wherein the waste paper pulp contains up to 7% by weight ground-wood. 55

9. A process according to claim 1 substantially as hereinbefore described.

10. A process according to claim 1 substantially as described in any one of Examples XI to XIII. 60

11. Waste paper pulp whenever bleached by a process as claimed in any one of the preceding claims.

J. A. KEMP & CO.,
Chartered Patent Agents,
14 South Square,
Gray's Inn,
London WC1R 5EU.

Printed for Her Majesty's Stationery Office, by the Courier Press, Leamington Spa, 1975.
Published by The Patent Office, 25 Southampton Buildings, London, WC2A 1AY, from which copies may be obtained.